


















AMF THERMATEX® Mercure

- AMF THERMATEX® Mercure is a white ceiling panel featuring fine perforations, creating a modern, high-quality surface finish
- Good sound absorption (0.60 α_w)
- Good light reflectance (85%)
- Ideal for retail, offices and meeting rooms, installations rooms or production areas



Edge details Additional edge details on request		Board 	Tegular 24 	Tegular 15 														
Thickness (mm)		15	15	15														
Dimensions (mm) Additional sizes on request		600 x 600 1200 x 600	600 x 600	600 x 600														
System		Exposed demountable - System C Exposed - Bandraster, demountable - System I.3 Exposed - Corridor, demountable - System F.3																
Weight		3.6 - 3.8 kg / m ²																
Colour		White																
Sound absorption		<div>EN ISO 354</div> <div>α_w = 0.60 as per EN ISO 11654 - Class C</div> <table><tr><td>Frequency f (Hz)</td><td>125</td><td>250</td><td>500</td><td>1000</td><td>2000</td><td>4000</td></tr><tr><td>α_p</td><td>0.45</td><td>0.40</td><td>0.50</td><td>0.70</td><td>0.70</td><td>0.65</td></tr></table> <div>NRC = 0.60 as per ASTM C 423</div>			Frequency f (Hz)	125	250	500	1000	2000	4000	α_p	0.45	0.40	0.50	0.70	0.70	0.65
Frequency f (Hz)	125	250	500	1000	2000	4000												
α_p	0.45	0.40	0.50	0.70	0.70	0.65												
Sound attenuation		<div>EN ISO 10848-2</div> <div>$D_{n,f,w}$ = 32 dB as per EN ISO 717-1</div>																
Sound reduction		<div>EN ISO 10140-2</div> <div>R_w = 21 dB as per EN ISO 717-1</div>																
Fire reaction		Euroclass A2-s1, d0 as per EN 13501-1 <div>RUS KM1 (G1, V1, D1, T1) as per FZ 123</div>																
Light reflectance		85%																
Thermal conductivity		λ = 0.060 W/m K as per EN 12667																
Humidity resistance		95% RH																
Indoor air quality		 A+	 E1															
Cleanability																		
Sustainability	 37-48%	 BIOSOLUBLE WOOL EC 1272/2008 Annex Q																

Products may vary from country to country.
Please contact your local sales representative.
For further information and legal notice, please visit our website.